## $\Lambda$ UTOM $\Lambda$ T $E_{TM}$

# Surface Mount Wall Switch - 5Ch

The Automate range of controllers offers the Surface Mount Wall Switch - 5Ch, an easy mount wall switch that screws directly to the surface of the wall, allowing simple installation.



#### FIVE CHANNELS

Activate shades individually or within customised groups with five programmable channels.



#### MAGNETIC BACKING PLATE

Install using the magnetic backing plate to use the control panel as a removable remote.



#### FIXED BACKING PLATE

Install using the secure backing plate to use the control panel as a fixed wall switch.



#### SIMPLE WALL ATTACHMENT

Screws directly to the surface of the wall with no wiring or cutting required and is compatible with any Automate system.







### PRODUCT SPECIFICATIONS

Part #: MTRF-WS5-FLUSH - RF White 5CH Decorator Wall RF Switch (Flush)

Voltage	3V (CR2430)	Transmission Distance	20 Meters typical (Up to 100 Meters unobstructed)
Radio Frequency	433.92 MHz		
Transmitting Power	10 milliwatt	RF Modulation	FSK
Operating Temperature	-10°C to 50°C	IP Rating	4X
	14°F to 122°F		
Legacy Option	NO		

#### **APPLICATIONS**

- Roller Shade
- Roman Shade
- Awning Shade

- Venetian Shade
- · Curtain Shade



