

PROGRAMMING INSTRUCTIONS MANUAL

Solar Powered Wind & Light Sensor



 $AUTOMATE^{\scriptsize @} \ | \ Wind-Light \ sensor \ is \ a \ device \ for \ measuring \ wind \ speed \ and \ light \ intensity.$ The information is transmitted to ARC outdoor motorized shades that will move to their top or bottom limits.

FEATURES:

- Measure wind speed with an anemometer
- Measure light intensity with a Lux meter
- LCD display
- ARC compatibility
- USB-C Charging Port*
- Solar Charging Panel*
- Loss of communication Safeguard Technology
- AC Input**

- * With MT02-0301-072001 only
- ** With MT02-0301-072003 only

CONTENTS

| 1 | INSTALLATION | 4 |
|-----|--|----|
| 2 | OVERVIEW | 5 |
| 2.1 | Components | 5 |
| 2.2 | LCD Display | 6 |
| 2.3 | Safeguard Technology | 6 |
| 2.4 | Waking the device | 6 |
| 2.5 | Charging the wind & sun sensor | 7 |
| 3 | SETUP | 7 |
| 3.1 | Pair the motor to a remote (if required) | 7 |
| 3.2 | Check motor Direction | 8 |
| 3.3 | Pair or Unpair the Sensor to a Motor using a Pre-Paired Remote | 8 |
| 3.4 | Setup wind speed control | 9 |
| 3.5 | Setup light control | 9 |
| 4 | ADDITIONAL FUNCTIONS | 10 |
| 4.1 | Display measured wind speed & light intensity | 10 |
| 4.2 | Display the pre-set threshold value | 10 |
| 4.3 | Wind Sensor Function | 11 |
| 4.4 | Light Sensor Function | 11 |
| 4.5 | Activate/Deactivate Sun & Wind sensor functionality on the motor | 12 |
| 5 | TROUBLESHOOTING | 13 |

SAFETY INSTRUCTIONS

WARNING: Important safety instructions to be read before installation and use.

Incorrect installation or use can lead to serious injury and will void manufacturer's liability and warranty.

It is important for the safety of persons to follow the enclosed instructions. Save these instructions for future reference.

- Do not submerge in water or expose to extreme temperatures.
- Persons (including children) with reduced physical, sensory or mental capabilities, or lack of experience and knowledge should not be allowed to use this product.
- Use or modification outside the scope of this instruction manual will void warranty.
- Installation and programming to be performed by a suitably qualified installer.
- Follow installation instructions.

- For use with motorized shading devices.
- Keep away from children.
- Frequently inspect for improper operation. Do not use if repair or adjustment is necessary.
- · Keep clear when in operation.
- · Replace battery with correctly specified type.

Rollease Acmeda declares this equipment is in compliance with the essential requirements and other relevant provisions of R&TTE Directive 2014/53/EU

Statement Regarding FCC Compliance

This device complies with Part 15 of the FCC Rules / Innovation, Science and Economic Development Canada's licence-exempt RSS(s). Operation is subject to the following two conditions:

(1) This device may not cause harmful interference, and (2) This device must accept any interference received, including interference that may cause undesired operation.

L'émetteur/récepteur exempt de licence contenu dans le présent appareil est conforme aux CNR d'Innovation, Sciences et Développement économique Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes :

1. L'appareil ne doit pas produire de brouillage; 2. L'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications.

However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.



IMPORTANT INFORMATION

Each motor can only be paired with one sensor at a time. It is not possible to connect multiple sensors to a single motor, including any combination of, but not limited to:

- Sun & Wind Sensor + Motion Sensor
- Internal Sun Sensor + Motion Sensor
- Two Sun & Wind Sensors
- Two Motion Sensors
- Two Internal Sun Sensors

If a new sensor is paired with a motor, it will override the previously paired sensor. Multiple motors can be paired to one sensor. E.g., one Sun Sensor and three motors.



Do not dispose of in general waste. Please recycle batteries and damaged electrical products appropriately.



I INSTALLATION

MT02-0301-072001:

- 1. Find an appropriate location with direct sunlight and in a location that will see the same wind conditions the paired device will see.
- 2. Remove the base covers
- 3. The solar panel must be face up and in direct sunlight
- 4. Fix the sensor to a suitable surface
- 5. Re-attach the base covers
- 6. Ensure the three rotating cups are in an approximately horizontal position


MT02-0301-072003:


Note: Installation by licenced electrician only.


- Find an appropriate location with direct sunlight and in a location that will see the same wind conditions the paired device will see
- 2. Cut off the mains power supply
- 3. Remove the base covers
- 4. Complete wiring into the provided terminal block.
- 5. Ensure that the luminosity sensor orientation face up and in direct sunlight
- 6. 6. Fix the sensor to a suitable surface
- 7. Re-attach the base covers
- 8. Ensure the three rotating cups are in an approximately horizontal position


Transmission Distance:

35 meters indoors 200 meters open space










2.1 COMPONENTS



^{*} With MT02-0301-072001 only

^{**} With MT02-0301-072003 only

2.2 LCD DISPLAY



- 1. The LCD screen lighting stays active for 30 seconds. If there is no operation, the sensor automatically switches its screen off for energy saving, but the program will keep running for normal detection and command transmissions. When the screen is off, pressing any (non-reset) button triggers the screen to be on again for another minute.
- 2. Sun icon: indicates the light intensity detection mode.
- 3. Flag icon: indicates the wind speed detection mode.
- 4. Battery icon: The voltage of the internal battery is checked by its inner program once every day. The appearance of this battery icon indicates that its voltage is below 2.7V. It is recommend that the sensor is placed in direct sunlight or plug in a USB-C cable to charge the sensor for minimum of 6 hours.
- * 5. RF signal icon: displayed when transmitting a signal.
 - * With MT02-0301-072001 only

2.3 SAFEGUARD TECHNOLOGY

Once the sensor is paired to an Automate external motor, the sensor will check in with the motor every 30mins

If the motor does not receive the signal at the checkpoint, the motor will close as a protective measure.

Once the Safeguard feature has been triggered, motor will only move in small increments. This is different from the timeout function after the wind or light function has triggered, which will not allow you to control the shade until the time has elapsed.

This is different from the timeout function after the wind or light function has triggered, which will not allow you to control the shade until the time has elapsed.

*This is a sign that there is a fault in the sensor or that the internal battery has gone flat. If this happens, you will need to place the sensor in direct sunlight or plug in a USB-C cable to charge the sensor for minimum of 6 hours.

2.4 WAKING THE DEVICE

NOTE:

If the screen is off, press any button once to wake the device before performing any actions described in this manual. The screen must be active for the device to register further inputs.



With MT02-0301-072001 only

2.5 CHARGING THE WIND & SUN SENSOR

NOTE:


It is recommended to charge the sensor before going to site.

Plug in a type-C cable and charger. It may take several hours to charge the battery.

To check the battery, press any button to turn on the screen (if the display is blank)


Unplug the cable from the sensor. Refer to the below table for the status.

| ICON | |
|---------------|--------------|
| Static Static | <20% Battery |
| (No Icon) | Charged |
| Flashing | Charging |



3 SETUP

3.1 PAIR THE MOTOR TO A REMOTE (IF REQUIRED)



NOTE:

- Complete setup using motor programming instructions.
- The sensor will only work if the motor is configured with the upper and bottom limits.

3.2 CHECK MOTOR DIRECTION

Confirm that motor direction is setup as below so any paired sensors will activate correctly.


DOWN on the remote OPENS the Awning (awning moves in an outward/downward direction).

E.g.




And **UP** on the remote CLOSES the Awning (awning moves in an inward/upward direction).

E.g.



Note: Follow motor programming instructions to reverse motor direction if necessary.

3.3 PAIR OR UNPAIR THE SENSOR TO A MOTOR USING A PRE-PAIRED REMOTE



NOTE:

- If the pair is successfully done, the motor can be triggered to move upward by pressing the UP button on the sensor.
- Ensure the wind and light sensor functionality on the motor is enabled prior to pairing the wind and sun sensor.
- The pair relationship is kept even if the motor power is reset or the sensor is reset to its default setting.

3.4 SETUP WIND SPEED CONTROL

Press & Hold **M** button for 2 seconds until screen flashes




Cycle though settings until you have the Wind icon(►) by pressing M



Adjust the pre-set threshold by pressing **UP** to increase value or **A** to decrease value







NOTE:

- The wind speed control function can be disabled by setting its threshold to ZERO. Other threshold values enable this function.
- It is recommended to set the default wind speed threshold to 25 km/h for optimal performance.
- The wind sensor has priority and will override the sun sensor functionality if both are enabled.
- It is recommended to keep the sun sensor disabled (set to 0) to prevent potential conflicts with the wind sensor operation.

3.5 SETUP LIGHT CONTROL

Press & Hold **M** button for 2 seconds until screen flashes





Cycle though settings until you have the Sun icon(☀) by pressing M





Adjust the pre-set threshold by pressing **UP** to increase value or **A** to decrease value



UP P2




NOTE: The light intensity function can be disabled by setting its threshold to ZERO. Other threshold values enable this function.

Approx. Wait 10 seconds to set the threshold

| Condition | klux (approximate) |
|-----------------|--------------------|
| Direct Sunlight | 100 |
| Daylight | 10 |
| Overcast | 1 |

4.1 DISPLAY MEASURED WIND SPEED & LIGHT INTENSITY

In the sleep mode (blank screen), pressing the Adjust button (A) can loop through light intensity or wind speed. When the loop icon, \$\(\delta\), is present, the system will automatically display them in a cycle (5 seconds). The sequence is light > wind > loop (light).




4.2 DISPLAY THE PRE-SET THRESHOLD VALUE

Press the MENU button (M) repeatedly to display the pre-set threshold values in a cycle, the corresponding icon, * h, flashes to indicate that the pre-setting value is displayed. Pressing the MENU button (M) again returns to the normal mode. The sequence is: display the light intensity threshold value > display the wind speed threshold value > return to normal mode.



4.3 WIND SENSOR FUNCTION

Wind speed continuously exceeds the threshold value of wind speed for longer than 3 seconds



The sensor command is executed to control the motor "**UP**" action



To prevent the motorized shades from frequently opening and closing under a gust, the motor does not operate for next 8 minutes



4.4 LIGHT SENSOR FUNCTION

When the environmental light intensity is higher than the threshold for 15 minutes



The sensor command is executed to control the motor "**DOWN**" action



After this period, the sensor temporarily disables its light detection for the next 15 minutes



When the environmental light intensity is lower than the threshold for 15 minutes









After this period, the sensor temporarily disables its light detection for the next 15 minutes



NOTE:

- Wind sensor trigger overrides light sensor, and moves motor up to top limit, despite motor having moved down due to strong light.
- It is recommended to keep the sun sensor disabled (set to 0) to prevent potential conflicts with the wind sensor operation.

4.5 ACTIVATE/DEACTIVATE SUN & WIND SENSOR FUNCTIONALITY ON THE MOTOR

Note: Functionality activated by default.





Motor Response



Press **UP** on controller



Motor Response



Press STOP on controller



Motor Response (Activated)



Motor Response (Deactivated)



5 TROUBLESHOOTING

| Problem | Cause | Remedy |
|---|--|--|
| Notor is not responding | *Sensor battery is discharged | Recharge battery with a USB cable |
| | Radio interference/Shielding | Ensure transmitter is positioned away from metal objects and that the motor aerial/receiver is kept straight and away from metal |
| | Receiver distance is too far from transmitter | Move transmitter to a closer position |
| | Power failure | Check the connection from power supply to motor |
| | Incorrect wiring | Check if wiring is connected correctly |
| | Pairing error | Press UP button on sensor to verify pairing |
| | The motor's function of detecting wind/light is off | Turn on the function |
| Motor extends then constantly | Wind or light threshold is too low | Increase the threshold to reduce sensitivity |
| retracts unexpectedly | Extend motorized shade is casting shadow onto sensor | Check & reposition sensor if necessary |
| | Wind sensitivity is too high or too low | Adjust sensitivity |
| Motor does not react to wind or light setting | Time interval of strong wind is less than 8 minutes | The wind triggering time length must be over 8 minutes |
| | Time interval of light is less than 15 minutes | The light triggering time length must be over 15 minutes |
| Screen not turning on | *Internal Battery Flat | Place sensor in direct sunlight or plug in the USB-C connection to charge sensor for minimum of 6 hours. |
| Motor is only moving in small increments (after motor setup has been completed) | Safeguard feature | Communication between motor and sensor has been lost. Replace the 2 x alkaline batteries and check motion sensor is working correctly. |
| Motor retracted and not operating (not getting stepping mode function) | Wind Sensor has been triggered | Once the Wind sensor has been triggered there is an 8min lockout as a protective measure. |
| Safeguard feature is not triggering | Motor and Wind sensor checking timing | Motor and Wind sensor need to have at least 1 check in before this feature is enabled, this occurs every 30mins. |

^{*} With MT02-0301-072001 only

NOTES

NOTES